

Micro
















Micro 2020 — the square solution

Vertical awning for glass roofs and wide window expanses



Glass roof

On glass roofs in the Murano series from Lewens, the Micro 2020 can be mounted optionally from inside on the gutter or purlin and post, so that only the fabric is visible from the outside, or it can be inserted flush in the aperture.





Equipment and convenience features

- Width max. 600 cm, height max. 270 cm
- Zip guide and patented balance spring technology
- Electric motor with obstacle recognition
- Awning fabric:
 Screen glass fibre fabric (standard),
 Acrylic, polyester (option, up to max. 220 cm in height)
- Options:
 Radio motor with obstacle recognition/ radio remote control, automatic weather sensor, various attachment options



Square

The square shape and flat, push-on end caps make the Micro 2020 the perfect choice for installation flush with the façade or for niche installation.

Screen

Screen glass fibre fabric is ideal for use on glass roofs or facades, as it ensures optimal shade and glare protection while affording views of the outside.



The Micro 2020 was conceived as a vertical awning especially for openings in the case of glass roofs and conservatories and for the wide window panes of panorama windows. Patented balance spring technology and a zip guide, which guides the fabric concealed in lateral tracks, ensure a taut sit of the awnng fabric. Screen glass fibre fabric ensures privacy and shade while retaining a view of the outside.



Window and façade

Smaller-format Micro 2020 awnings can be mounted on the façade or inside the window soffit without additional brackets.



Closed guide [Z]

Track with lateral zip guide
and patented balance spring technology
for higher fabric tension, a smooth sit
of the awning, greater wind safety
and improved lateral compensation
for building tolerances.

Micro 2020

Equipment and technical features





Manufactured and assembled in Germany



Quality and technology



Recipient of the iF DESIGN AWARD

Туре	Angular
Fabric guide	Closed guide (Z)
Cassette (H x D), approx.	110 x 113 mm
Unit width [max.]	
1 unit (single panel)	600 cm
System height [max.]	
Ordering height	270 cm
Drive	
Electric motor (for wall switch)	
with obstacle recognition	
Radio motor (io)	
Frame colours	
17 RAL colours and 6 textured finishes (Lewens standard colours)	
Natural silver (E6/EV 1 anodized, small components RAL 9006)	
Additional RAL, special colours and effect finishes	
Awning fabrics from the LEWENS collection	
Screen glass fibre fabric	
Branded acrylic (spun-dyed, ultra fade resistant)	* 🗆
Branded polyester (spun-dyed, ultra fade resistant)	* 🗆
Options	
Radio motor with obstacle recognition + radio remote control (io)	
Automatic weather sensor (sun, wind, rain)	
Attachment	
Wall / ceiling	
Murano glass roofs (below or behind gutter or purlin)	
Other makes of glass roof	in preparation

* up to max. 220 cm in height

Possible dimensions and restrictions along with the complete range of electronic accessories can be found in the technical data in the current Lewens price list.



Your stockist will be happy to advise you:

